



AUTOMATIC WATER SOFTENER GIX12



WATER NETWORK
CONNECTIONS



1/2" G



3/4" G

MIXER

TECHNICAL DATA

Weight		15 Kg
Power supply	standard	230V 50/60 Hz
	optional	120V 60 Hz
Maximum flow rate		1500 l/h
Room temperature		4°C -30°C
Power requirement		4 W
Regeneration salt amount		1.4 kg
Maximum salt content in the brine tank		25 kg

SUPPLY WATER CHARACTERISTICS

Drinking water		
Crystal-clear water (SDI 1)		
Temperature		4°C-25°C
Pressure		2 bar - 8 bar
Maximum hardness		90 °f

1 WATER SOFTENER CONSISTING OF:

- 1 brine tank
- 1 Autotrol 255/740 Logix valve
- 1 cylinder of 12 litres holding 8.5 litres of cationic resins adapt for softening
- 1 instruction manual
- 3 m of unloading pipe
- 1 overflow curved union joint
- 1 fitting for the unloading pipe
- 1 chlorine generator (OPTIONAL)

PRODUCT CODE:

- ABX02 with connections 1/2" G
- ABX05 with connections 3/4" G mixer

THE WATER SOFTENER IS SUITED FOR:



LITRES OF SOFTENED WATER ACCORDING TO ITS HARDNESS

°f	20	30	40	50	60	CYCLIC CAPACITY [m ³ .°f]
°d	11	16	22	28	33	
ppm CaCO ₃	200	300	400	500	600	
	2520	1680	1260	1008	840	50.4